

LIONCAT 20

产品成分:

阳离子表面油，为天然高熔点蜡质化合物。

技术指标:

外观	白色膏状
有效物含量	20% (± 2)
电荷	阳离子
密度 (磅/加仑)	8.2 (± 0.2)
pH (10% 溶液)	4.0 – 5.0
储存稳定性	室温下，1 年。 最佳储存温度为 15°C -30°C。
凝固/融化稳定性	对低温敏感。要求储藏温度不低于 5°C
耐光性	好
耐电解质性能	好
乳化性	使用前乳化。 易溶于热水。 与热水以 1:1 均匀混合。 30°C -60°C 时，与水以 1:4 进行乳化。

主要性能:

Lioncat 20 通常用做表面油，以获得丰富而具有蜡感的表面手感。在干燥中也作为离板剂使用。

- 赋予皮面独特的丝绸手感。
- 在干燥中优异的离板性能。
- 赋予摔软革柔软手感。
- 使用时浓度不宜过高。

The Supplier makes no warranty of any kind, expressed or implied, concerning this product or its use. The user assumes all risk of use or handling, regardless of whether the same is in accordance with the direction or suggestion of the supplier.

应用说明:

以削匀蓝革重量计算 表面油	1.0%-2.0%，于工序末尾。
离板剂	0.75% - 1.0%，于工序末尾。
摔软碎石纹革	1.0% - 2.0% Lioncat 20
家具革	1.0% - 2.0% Lioncat 20
全粒面纳帕革	0.5% - 2.0% Lioncat 20
绵羊、山羊、小牛革	1.0% - 2.0% Lioncat 20
鹿皮手套革	1.0% - 2.0% Lioncat 20 以坯革重计

The Supplier makes no warranty of any kind, expressed or implied, concerning this product or its use. The user assumes all risk of use or handling, regardless of whether the same is in accordance with the direction or suggestion of the supplier.