

SOFTOIL LP-400

COMPOSITION:

Softoil LP-400 is a high grade sulphonated fish oil.

SPECIFICATIONS

Appearance	Amber Liquid
Activity	68 - 72 %
Charge	Anionic
Density (Lb/Gal)	8.3 (± 0.2)
pH (10% Solution)	6.0 – 7.0
Storage Stability	1 Year at room temperature Optimum storage temperature is between 15°C and 30°C.
Freeze/Thaw Stability	Not Sensitive to Freezing. After freezing heat to 25°C to 30°C and mix well until homogeneous.
Lightfastness	Good
Electrolyte Stability	Very Good
Emulsification	Mix before use. Readily soluble in warm water. Emulsify 1:4 at 30°C to 60°C

KEY PROPERTIES:

Softoil LP-400 is a specially developed economical fish oil to produce leathers where a high degree of softness is required. Leathers produced with Softoil LP-400 will retain softness for longer periods of time.

- A highly penetrating oil and co-product with other anionic fatliquors.
- Good lightfastness properties.
- Excellent electrolyte stability in Chrome retanning and hard water applications.
- Imparts excellent tensile strength.
- Aids in penetration and softening action of other fatliquors when used in retan.

APPLICATIONS:

Recommended usage is 2% to 14% on Blue shaved weight.

The Supplier makes no warranty of any kind, expressed or implied, concerning this product or its use. The user assumes all risk of use or handling, regardless of whether the same is in accordance with the direction or suggestion of the supplier.