

Tannin™ Has It.

LIONWAX FW-1

tannincorp.com

COMPOSITION

A wax and oil blend designed to give a rich surface feel and pull up to water-resistant leathers.

SPECIFICATIONS

Appearance	Yellow wax
Activity	100%
Melting Point	40 - 50°C
Charge	No charge
Density (Lb/Gal)	6.8 (± 0.2)
Solubility	Insoluble in water.
Storage Stability	Indefinite at optimum storage temperature between 15°C and 30°C.
Freeze/Thaw Stability	Not sensitive to freezing.
Emulsification	Insoluble in water. Melt to 50-60°C before use.

KEY PROPERTIES

LIONWAX FW-1 is a soft wax that can be used alone to produce stuffed, semi-stuffed, or pull-up leathers on a heated roll coater.

- Good filling of leathers
- Does not adversely affect Maeser Flexes
- Clean and level colors
- Good pull-up effects

APPLICATIONS

8 – 24 gm / sq ft @ 60 - 80°C on a heated Roll Coater.

Best applied in two separate coats.



Tannin Corporation
65 Walnut Street
Peabody, MA 01960, USA
Phone: +1.978.532.4010
Fax: +1.978.532.5536
sales@tannincorp.com

Tannin Mexico S.A. de C.V.
Blvd. San Crispin 130
Fracc. Ind. San Crispin
Leon, Gto. 37527, Mexico
teléfono: +52.477.770.9499
tanninmex@terra.com.mx